

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
21 August 2003 (21.08.2003)

PCT

(10) International Publication Number
WO 03/069757 A1

- (51) International Patent Classification⁷: **H02J 3/18**,
G05F 1/70
- (21) International Application Number: PCT/SE03/00015
- (22) International Filing Date: 7 January 2003 (07.01.2003)
- (25) Filing Language: Swedish
- (26) Publication Language: English
- (30) Priority Data:
0200050-3 9 January 2002 (09.01.2002) SE
- (71) Applicant (for all designated States except US): **ABB AB**
[SE/SE]; S-721 83 Västerås (SE).
- (72) Inventors: and
- (75) Inventors/Applicants (for US only): **BIJLENGA, Bo** [SE/SE]; Lilla Ringvägen 2, S-662 33 Ämål (SE).
- (54) Title: EQUIPMENT AND METHOD FOR EXCHANGING POWER, IN SHUNT CONNECTION, WITH AN ELECTRIC POWER NETWORK, AND USE OF SUCH EQUIPMENT
- (81) Designated States (national): AE, AG, AI., AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]



(57) Abstract: Equipment for exchanging power, in shunt connection, with an electric power network (N) comprising a reactive impedance element (C, LC) and a voltage source converter (VSC) for mutual connection in series. The power network has a nominal voltage (U_n) of a fundamental frequency (f) and a given phase position. The converter is intended for generating a fundamental-tone voltage (US) within a control range (A) which limits the amplitude of the fundamental-tone voltage. The control range limits the amplitude of the fundamental-tone voltage to a value which is lower than the nominal voltage of the power network and comprises generation of a reactive component (US_r) of the fundamental-tone voltage with a phase position (ϕ) that either coincides with the phase position for the voltage of the power network, or that deviates by 180° electrically from the phase position for the voltage of the power network.

WO 03/069757 A1